



UNIT 5 HAZELFORD WAY INDUSTRIAL ESTATE, NEWSTEAD
NOTTINGHAM, ENGLAND. NG15 ODQ
+44 (0) 844 414 0987 | info@printchem.co.uk | www.printchem.co.uk

PC600 – CHEMSOL – TECHNICAL DATA

Product Summary

PC600 is a sheetfed and web offset fountain solution designed for all types of dampening systems. This is free from gum Arabic with excellent wetting of the plate, to give improved ink densities and sharper images.

PC600 is designed for use in hard and soft water areas (dose accordingly), and is formulated with tightly controlled corrosion inhibition and anti mould inhibitors to help keep a cleaner running system that will last longer without the need to continually replace parts due to excessive wear and/or build up.

Properties

Flashpoint:- NA

Colour:- Pale Green

State:- Liquid

Ph:- 4.7-5.5

Solubility:- Soluble with water

VOC: approx. <5%

Packaging:- 25litre, 205litre, 1000litre all available

Recommended shelf-life:- 12 months

Storage:- Store between 5 and 30C for best results.

Labelling:- GHS07: Exclamation Mark

Method of Use

A typical recommended dosage of 2-4% per litre of Hard water or 1-2% per litre of soft water, however the ideal dosage can vary depending on press and local conditions therefore may require testing prior to full production run.

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

For any further information please contact the technical department at Printchem